

Models

PD-1600Q
PD-3200Q
PD-4800Q

Description

Three power Configurations; 4 channel 3 channel or 2 channel. Individual 4 channel inputs and 2 channels inputs. Independent volume control 4 channels, independent signal indication, Independent clip indication Bridge mode switch for channel 1 & 2 and channel 3&4. The PD-Quad channel series offer maximum flexibility without compromising on power or performance. The PD-1600Q comes with additional bass and treble controls



Specifications

Model	PD-1600Q	PD-3200Q	PD-4800Q
RMS Output Power (Per Channel, 8Ω)	4 × 200 W	4 × 300 W	4 × 600 W
RMS Output Power (Per Channel, 4Ω)	4 × 300 W	4 × 600 W	4 × 900 W
Rated Power (Bridge 8Ω)	2 × 300 W	2 × 600 W	2 × 900 W
Rated Power (Bridge 4Ω)	2 × 600 W	2 × 1200 W	2 × 1800 W
Input Sensitivity	0.775 V	0.775 V	0.775 V
S/N Ratio (A Weight)	>100 dB	>102 dB	>102 dB
Frequency Response (+0/-0.25dB)	20 Hz to 20 kHz		
Class	AB	AB	AB
Damping Factor	>200 : 1	>300 : 1	>300 : 1
THD (10% Rated Power)	0.05%	0.05%	0.05%
Input Connector	4 x XLR		
Input Impedance	20KΩ Balanced, 10 KΩ Unbalanced		
Output Connectors	Binding post		
Cooling	2 × Fan Airflow from front to back		
Power Supply	230 VAC / 50Hz		
Dimensions (H × W × D)(mm)	89 × 483 × 360	133 × 483 × 400	89 × 483 × 360
Net Weight (1 piece/pack)	16 Kgs	31 Kgs	37 Kgs
Gross Weight	19 Kgs	34 Kgs	40 Kgs