

## PSC234

### Features

- Stereo 3-way & sub woofer crossover
- Low / mid Crossover point between 200 hz to 700 hz
- Mid / high Crossover point between 1.5 kHz to 8 kHz
- Sub woofer frequency range between 20 hz to 200 hz
- Individual Controls for subwoofer, Low, Mid, High frequency
- Input / Output jack use XLR connectors
- Frequency response from 20~20 kHz +/- 1 db
- AC 120V/240V switchable
- 1U rack space

### Applications

Rental Companies | Install Audio | Theatre



### Specifications

Modes	3-Way stereo + subwoofer crossover
Input Connectors	XLR
Type	Electronically servo-balanced, RF filtered
Impedance	Balanced > 22k $\Omega$ , unbalanced > 10k $\Omega$
Max. Input level	+21 dB
Common Mode Rejection Ratio	>40 dB, typically >55 dB at 1kHz
Output Connectors	XLR
Type	Electronically servo-balanced, RF filtered
Impedance	Balanced 1.2 $\Omega$ , Unbalanced 600 $\Omega$
Max. Output level	+21 dBm
Dynamic Range	>160 dB, unweighted
Frequency Response	20 Hz to 20 kHz, $\pm$ 1 dB
Low/Mid Crossover	20 Hz to 700 Hz
Mid/High Crossover	1.5 kHz to 8 kHz
Subwoofer frequency range	20 Hz to 200 Hz
Dimensions (LxDxH)(mm)	483 $\times$ 218 $\times$ 44
Net Weight	2.5 Kgs
Gross Weight	3 Kgs